

LP Gas Hose

G01 Series

Description :

The KAIFLEX Liquefied Petroleum Gas Hose (LP Gas Hose) - G01 Series is made by double layers of polyvinyl chloride (PVC) with imbedded reinforced yarn (Polyester yarn). The LP Gas Hose has been certified with the UL 569 (Low pressure), UL 21 and CSA 8.3 (High pressure) standard. It is pressure resistant, anti-corrosion, liable for repeated bending and material complies with RoHS environmental requirements. Available in bulk or cut lengths.

Feature :

- Size : 1/4", 5/16", 3/8" (High pressure), 5/16", 3/8" (Low pressure)
- Material : PVC + Polyester yarn + PVC
- Color : Black
- Temperature Range : -40°C ~ 100°C
- Working Pressure Rating : 350psig (High pressure), 1psig (Low pressure)
- Flexibility : High
- Flammability Rating : FT4
- UV & Ozone Resistance : Yes
- RoHS Compliance : Yes
- Certificate : cCSAus (High pressure), CSAus (Low pressure), File No. : 303828

Application :

- Home burner system
- Heater equipment
- Gas discharging industry
- RV appliances



Specification :

LPG Hose	Nominal Conduit Size	Part Number	ID (mm)	OD (mm)	Bending Radius (mm)	Package (ft/m)
High Pressure	1/4	G01-H1/4B	6.15~6.73	13.12~14.26	102	305/100
	5/16	G01-H5/16B	7.73~8.31	14.62~15.76	102	305/100
	3/8	G01-H3/8B	9.32~9.90	15.62~16.76	102	305/100
Low Pressure	5/16	G01-L5/16B	7.73~8.31	14.62~15.76	32	305/100
	3/8	G01-L3/8B	9.32~9.90	15.62~16.76	39	305/100

